

Technical Data Sheet

| Size | | API Reg Pin | Recommended Make-Up Torque(KN.m) |
|---------|------------|-------------|----------------------------------|
| Inch | Millimeter | Inch | (KN.m) |
| 4-5/8" | 117.5mm | 2-7/8" REG | 6.1~7.5 |
| 6" | 152.4mm | 3-1/2" REG | 9.5~12.2 |
| 6-1/2" | 165.1mm | | |
| 6-3/4" | 171.5mm | | |
| 7-1/2" | 190.5mm | 4-1/2" REG | 16.3~21.7 |
| 7-7/8" | 200.0mm | | |
| 8-1/2" | 215.9mm | | |
| 8-5/8" | 219.1mm | | |
| 8-3/4" | 222.3mm | | |
| 9-1/2" | 241.3mm | 6-5/8" REG | 38~43.4 |
| 10-1/2" | 266.7mm | | |
| 12-1/4" | 311.2mm | | |
| 12-1/2" | 317.5mm | | |
| 13-1/2" | 342.9mm | | |
| 13-5/8" | 346.1mm | | |
| 14-3/4" | 374.7mm | 7-5/8" REG | 46.1~54.2 |
| 15" | 381.0mm | | |
| 15-1/2" | 393.7mm | | |
| 16" | 406.4mm | | |
| 17-1/2" | 444.5mm | | |
| 26" | 660.4mm | | |